

Selected Corro-Shield Self-Leveling Flooring

1. **Corro-Flor SL** (Ref. No. 300) (Regular, Fast Set and Extra Fast Set versions available).

Related Formulas:

Corro Hi-Flor (Ref. No. 301) (Regular and Fast Set versions available).

2. **Corro E-Crete SL** (Ref. No. 311)

3. **Corro-Crete SL** (Ref. No. 380)

Ref. No. 300 100% solids 3 part self-leveling floor system. Part C consists of filler pre-treated with Corro-Shield resins. Labor saving system. Good chemical resistance.

Ref. No. 301: Higher chemical resistant Novolac version of Ref. No. 300.

Ref. No. 311 Water-based ,3-part self-leveling epoxy cement with dense, hard aggregates. Heat resistant and cold resistant from -35°F / -35°C to 450°F / 232°C.

Ref. No. 380: 100% solids, 3 part self-leveling urethane concrete.

Note that the above listed formulas all conform to the ASTM C-884 test - (Thermal compatibility with concrete) making them excellent for environments requiring regular steam cleaning and wash downs.

The formulas listed above represent a selection of Corro-Shield products in this category. For product formulas with specific performance criteria not found in the above listed products, please contact; Sales / Technical Support at 1-800-298-7637 ext. 102 or tech.sales@corroshield.com.