

Selected Corro-Shield Trowel Flooring

1. **Corro-Flor** (Ref. No. 200)(Regular Set, Fast Set, Extra Fast Set, and Power Trowel versions available).

Ref. No. 200: 100% solids, 3 part slurry system. Designed for heavy traffic. Good chemical resistance.

Related Formulas:

Corro Hi-Flor (Ref. No. 201) (Regular and Fast Set versions available).

Ref. No. 201: Excellent chemical resistant Novolac version of Ref. No. 200. Designed for harsh environments.

Corro-Screed (Ref. No. 203)(Regular and Fast Set versions available).

Ref. No. 203: A dryer mix of Ref. No. 200 for spalled or scaling concrete.

Corro-Patch (Ref. No. 204)(Regular and Fast Set versions available).

Ref. No.204: Ref. No. 200 packaged in smaller units for patch-work – to address holes and cracks.

Corro-Flor Cove Base (Ref. No. 208)(Regular and Fast Set versions available).

Ref. No. 208: A different blend of Ref. No. 200 designed for coves.

Corro Elast-O-Flor (Ref. No. 205)(Regular and Fast Set versions available).

Ref. No. 205: 100% solids, 3 part slurry system with granite or quartz aggregate. Flexible elastomeric membrane. Highly resilient system designed to address vibration and movement. Very Good chemical resistance.

2. **Corro-E-Crete** (Ref. No. 219)

Ref. No. 219: Water-Based, 3-Part, Epoxy Cement with dense, hard aggregates. Heat Resistance and Cold Resistant from -35°F / -35°C to 450°F / 232°C

3. **Corro-Crete TR** (Ref. No. 280)

Ref. No. 280: 100% solids, urethane trowel slurry system.

Note that the above listed formulas all conform to the ASTM C-884 test - (Thermal compatibility with concrete) making them excellent for environments requiring regular steam cleaning and wash downs.

The formulas listed above represent a selection of Corro-Shield products in this category. For product formulas with specific performance criteria not found in the above listed products, please contact; Sales / Technical Support at 1-800-298-7637 ext. 102 or tech.sales@corroshield.com.