

Selected Corro-Shield Primers

1. **Corro Penetrating Seal** (Ref. No. 108)
2. **Corro-Prime** (Ref. No. 600) (Regular, Fast Set and Extra Fast Set versions available).
3. **Corro- Cure LV FS** (Ref. No. 602) (Regular Fast Set and Extra Fast Set versions available).
4. **Corro Elast-O-Prime** (Ref. No. 604)
5. **Corro Aqua-Cure** (Ref. No. 612)
6. **Corro All Purpose Primer** (Ref. No. 616)**
7. **Corro-Crete P** (Ref. No. 680)
8. **Corro Penetrating-Cote** (Ref. No. 106)

Ref. No. 108: Water-based, 2 part clear concrete sealer. Penetrates deep into the substrate. Corro-Shield's most commonly recommended primer. Prevents out gassing, blistering and dry spots.

Ref. No. 600: 100% solids, 2 part clear epoxy primer. For use on badly eroded concrete. Reduces dry spots in a trowel system overlay.

Ref. No. 602: 100% solids, 2 part moisture remediation / green concrete primer. Can be applied after initial set. Reduces moisture from 25 lbs / 1,000 SF to under 3 lbs. Reduces construction time of building projects and results in stronger substrates.

Ref. No. 604 100% solids, 2 part epoxy primer. For use when vibration is a concern. A primer for Elast-O-Cote (Ref. No. 104).

Ref. No. 612: Water-based, 2 part moisture remediation / green concrete primer. Can be applied after initial set. Reduces moisture from 15 lbs / 1,000 SF to under 3 lbs. Used extensively as a moisture vapour barrier in the flooring industry.

Ref. No. 616 Water-based, 1 part component primer used primarily for stainless steel bases and catwalks prior to the application of epoxy.

Ref. No. 680: Water-based, 3 part urethane concrete primer used under Corro-Crete TR (Ref. No. 280), Corro-Crete SL (Ref. No. 380) or Corro-Crete C (Ref. No. 282).

Ref. No. 106: Water-based, 2 part pigmented primer / coating. Pigmented version of Ref. No. 108 that may be used as an alternative.

Note that, with the exception of Ref. No. 616 ** (a metal primer), the above listed primers all conform to the ASTM C-884 test - (Thermal compatibility with concrete) making them excellent for environments requiring regular steam cleaning and wash downs.

The formulas listed above represent a selection of Corro-Shield products in this category. For product formulas with specific performance criteria not found in the above listed products, please contact; Sales / Technical Support at 1-800-298-7637 ext. 102 or tech.sales@corroshield.com.